

S. P. Howell-Jobsite 886

David L. Narver, Jr. Assembly Benches at stations 50 and 60

August 25, 1953

R

The following letters are quoted by permission:

UCRL letter COL 106L dated August 18, 1953.

"The following additional facilities are required at stations 50 and 60.

REFUGES - 10' x 12' x 8' high. Station 50

CABINETS - 10' x 12' x 8' high. Station 50

BENCHES - 10' x 12' x 8' high. Station 50

FIRE PLACES - 10' x 12' x 8' high. Station 50 each at side of benches

Benches to be of rugged construction, six feet long 37" high, 2 feet 6 inches deep with 1" plywood board. Top to be covered with masonite. It is requested that these benches be in place by completion of the buildings.

The above facilities are for U-1, etc."

LASL letter J-19-58 dated September 1, 1958.

"Reference is made to UCRL letter COL 106L dated 18 August 1953.

It is requested that earthenware tiles size be furnished Task Unit 14. Plywood may be substituted for masonite top covering and the term "of rugged construction" may be defined as being capable of supporting approximately one hundred pounds."

DEPARTMENT OF ENERGY LETTER NUMBER	J-19-58
SINGLE REVIEW AUTHORITY	Project Manager
REVIEWER (ADD)	ANSungall 7-23-9
NAME	J.D.Larson
DATE	7/29/58

David L. Narver, Jr.
Project Engineer

DLNJr:ih

cc: Project Manager
Construction Dept. (7)
Engineering Dept.
Project Engineering Office
751 Main Street
Oakland, Calif.

This document contains neither recommendations nor conclusions of the Department of Energy. It has been reproduced from the best available copy. It does not necessarily represent any official position of the Department of Energy, and its publication does not constitute an endorsement of any views or points of view expressed.

DOE FEDERAL INFORMATION SYSTEM
FEDERAL INFORMATION SYSTEM

DOE FEDERAL INFORMATION SYSTEM
FEDERAL INFORMATION SYSTEM