Acres 6 = 8-20



NOTES ON POGO STAFF MEETING (U) 5 December 1952

1/1991

PLANNING FOR CASTLE

PRESENT:

L. Asmodt L. Brown

A. Embry

G. Felt

A. C. Graves J. Malik G. Cowan

W. Ogle H. Plank

F. Reines

L. Seely

H. Smith R. Spence

B. Watt R. Wilson

411429

MODELS PROPOSED FOR TEST

Operation Castle, the next overseas test, was discussed in general terms at a DIRX meeting on 1 December, at which Bradbury stated that: (a) the operation, originally planned for this fall, will be delayed until Spring, 1954, and (b) the Laboratory will plan on testing the following four models:

DELETED (2) BELETED DELETED

DELETED DELETEL DELETEU

DELETED

DELETED

DELETED

DELETED

DELETEL

The schedule calls for completion of designs by April 1953, completion of construction by the end of 1953, and delivery at the test site by 1 March 1954. Since this constitutes a rather large program for the Laboratory, the feeling is that there can be few changes from this general outline; that is, it will take all the time available to get these bombs designed and

In addition, Berkeley will test the following two models:

(5) DELETEU

DELETED

fabricated, so it seems unlikely that more gadgets will be added for test.

(6)

BEST COPY AVAILABLE

This document consists of 7 pages. BOLD OF THE PARTY OF THE PARTY

J-15277

1-0501291



Sanitized by NN-523 on 2/5/98

att 22



These we need consider only from the point of view that they will be in the same operation, and their geographical location; we will not be concerned with making measurements on them.

DELETED

DELETED

That is, their design will include weapon characteristics (tail fins and ballistic cases for air dropping, etc.) and by the time of Castle there will reputedly be some ready for the stockpile.

MELETEN

DELETED

DELETED

II. PROPOSED MEASUREMENTS

UELETED

DELETER

DELETED

Mark agreed with this in essence, adding that T Division would be happy for any other information which could be obtained simply and without complicating the choice of firing sites. They would, for example, be interested in alpha, but not enough to justify putting in extra installations.

DELETED

DELETED

DELETED

DELETER

DELETED

DELETED

However, considering all the other quantities it is desired to measure, one probably might as well measure alpha, and it makes a convenient signal to trigger scopes.

DELETED

DELETED

DELETED

Again, on the latter determination, T Division have said they would like us to attempt it if we believe the measurement has a fair guarantee of success, but if we think it is marginal and it requires exorbitant effort, not to try it.

DELETED

DELETED

DELETED

Hark would like to wait until after Upshot to answer this question definitely.



_			
ل م	lin.	GELETED	
<i>\</i>	GELETED		HLETED

Techniques and equipment locations for the proposed measurements are discussed in more detail below.

III. FIRING SITES

If we assume that at least four of the six models mentioned will have yields in the megaton region, the worry promptly arises of in one operation firing several gadgets which can lead to extremely bad fall-out. Presumably, one can take the necessary precautions to protect personnel, but there is also the possibility of having to stop the operation before completion because the islands are so contaminated that no one can work on them. During Ivy there was not any really serious fall-out hazard: the radioactivity did not get down to Parry at all, but only to around Rumit; it was possible to work on Rumit the day after the shot, and a week later on Aomon. However, Ogle feels we were extremely fortunate and might not be so again.

In addition, there are the considerations of conservation of real estate, suitable locations for instrumentation, weapon assembly and other operational problems.

DELETED

DELETED

DELETED


DELETED

DELETER

DELETED

Wilson was asked about the possibilities of various crafts. A T-boat would cost about \$500,000, he thought, but he would not recommend it because with any winds it will take on water and roll in the sea. He would guess that a barge without fittings would cost something like \$55,000 - \$50,000, and suggested putting the barge inside an LSD, assembling the bomb there using the fittings available on the LSD, then floating the barge off. A 500-ton barge can go inside an LSD. Or one might use a larger barge, assemble inside the lagoon, and tow it out to sea if desired. He thought that if we are really serious about doing the shots at sea, it would be worth some study to see what types of vessels would be adequate. There may be several types of suitable landing crafts, or perhaps pontoon barges might be considered.

te Clubnaj



convenient to float the barge off Parry to work on it (weapon assembly, etc.), then float it across the lagoon and anchor it on the far reef.

Ogle questioned that there would be any appreciable difference in the fall-out from a gadget fired on a raft in the water and one fired as a surface shot on land, except that a few of the induced activities might be different. He thought it a good idea to use rafts but doubted that the width of the lagoon was enough to guarantee no fall-out hazard and thought they might have to be out in the ocean some 50 to 100 miles.

Felt and Graves did not think that fall-out would be serious from a shot in the lagoon, feeling that the situation would be more like an air drop. Felt pointed out there are two things to contend with: first, there is a pattern around the bomb which is essentially round--this is not fall-out but contamination from the base surge or whatever one chooses to call it. The real fall-out is rather unpredictable, but it follows the trade winds; Felt thought that after one is 10 miles away, it does not matter whether he is 15, 20, or 50 miles away.

Again, he felt there would be much less particulate matter thrown up in the air from a shot over water. Spence pointed out that actually one is putting quite a lot of debris in the air, since three per cent of sea water is composed of solids. However, he did not know in what structure this would come down, or whether it would remain suspended in the air.

Ogle was still worried about fall-out, not as a danger to people but from the point of view of having to stop in the middle of an operation because of not being able to work on an island scheduled for the next shot.

DELETED

DELETED


UELETED

17

Sampling planes for a Bikini shot could be based on Eniwetok Island (200 miles away), an advantage over basing them on Kwajalein. Bikini is almost due east from Eniwetok. In the spring the winds are all westerly except at the surface, where there is a shear.

Instrumenting a raft shot should not be too difficult for yield measurements only. In view of the present situation on Mike Shot, and since these are also thermonuclear models, it is felt one wants to get both radiochemical and fireball yield. The former can be done with almost any firing site. Felt thought that fireball photography would be no problem on such a shot; pictures could either be taken from a ship using a gyrostabilized platform or from an island if the raft is in the lagoon.

086106001





Spence suggested an additional advantage to the barge: this will probably not be the last megaton operation nor the last in which air drops are not feasible, and we will always need land. Another method for firing is obviously in order, and use of barges should at least be tried out.

•		
DELETED		DELETED
	DELETED	

Everyone liked the idea of using rafts, both to save land and because of the flexibility they afford, particularly if they can be employed in the lagoon. Ogle was still worried about fall-out; Spence did not think one could ever be completely happy about fall-out, but personally did not think there was too much to worry about. Graves thought one could in the future avoid such wind patterns as led to the bad fall-out on Greenhouse Dog and Item.

After further discussion, it was agreed to plan tentatively upon using rafts for the models mentioned, pending Holloway's approval from the point of view of the weapons. Wilson will look further into the raft situation and get more information on dimensions, construction, and other details. There would, incidentally, be no problem in towing a barge from Enivetok to Bikini, should this become desirable.

DELETED

III. TENTATIVE SHOT SCHEDULE

After considerable discussion, the following schedule appeared reasonable as a basis for planning:

Region of Teiteiripucchi Reft Reft Reft Reft Reft Reft Reft Reft	Shot	Site '	Suggested Time Interval Between Shots*
Region of Teiteiripucchi 7 Bikini Reft 10		Raft or Runit	14 m = 1
DELETED BIRINI Reft 10	DELETED	Eberiru	10
Reft 10		Region of Teiteiripuc	ahi a
Raft 10	UELETEN	Bikini	
	1 0	Raft	
		Raft	

Very tentative -- based on Berkeley's having two crews in the field, and J-11's request for 10-day interval between shot sample arrivals at LASL.

Comments

DELETED

BELETER

SELETED

DELETED

TELETED DELETED Details of the tower, etc., are up

to Berkeley. They will do their own radiochemistry. Incidentally, work is in progress for filling up the Eberiru crater.

DELETED

DELETED

DELETED

example, it may be possible to use Krause's station on Bogon for the time history measurement, in which case we would want, if not land, at least not deep water between zero and that station. It is also not yet clear what installations might be required for special photography.

It appears that a photo tower on Parry could cover, from the point of view of yield, all the above shots at Enivetok.

IV. FURTHER DISCUSSION OF CASTLE MEASUREMENTS

A. Photography

Bo far, we are talking of nothing but ball-of-fire photography, but it seems appropriate that some study be given to use of the photographic technique for other measurements which T Division might ask for.

B. Alpha

While the feeling at the moment seems to be that alpha measurements are not absolutely necessary, interest in them has not been completely disclaimed, so it behooves us to investigate ways to get alpha by comparatively simple, remote means. J-13 is looking into the Teller alpha technique, possibilities of telemetering the signal, etc., and will continue these studies.

C. Measurement of Interval Between Two Bombs

Several methods are possibilities:


1. Teller light - a. photocells b. Bowen cameras

DELLILL

DELLETELL

This station will accommodate photocells or photomultipliers. Stewart used this technique on Ivy and it worked admirably.

1-0501088



T Division has talked about an accuracy of + 20% with regard to this determination. Felt stated that a Bowen camera, looking directly with no mirrors or pipes, could get it this well.

2. Gamma Rays

This technique depends upon the possible location of a station. Malik thought the measurement would be possible at 4000 yds and with two scopes.

3. Electromagnetic

The feasibility of this technique has not yet been proved. On Mike Shot, the time interval as measured by C. Cowan was about 1 usec longer than with other techniques; the reason for this is not understood at the moment.

Watt was requested to give some thought to the above methods and present his recommendations.

DEETEN

DELETED

DELETED

. Members of the group will study the problems involved and further discussions will be held in a week or so.

Notes Edited By: W. E. Ogle/diw:ak

Distribution:

1 of 15/A - A. C. Graves

2 of 15/A - S. W. Burriss

5 of 15/A - B. Brixmer
4 of 15/A - R. Campbell
5 of 15/A - J. Clark, G. Felt, R. Houghten

of 15/A - C. Cowan

7 of 15/A - P. Gelentine

8 of 15/A - A. Knauf

9 of 15/A - W. Ogle, L. Seely, A. Embry

10 of 15/A - H. Plank

11 of 15/A - F. Porzel

12 of 15/A - W. H. Smith, J. Malik

13 of 15/A - R. Spence

14 of 15/A - B. Watt, L. Asmodt

15 of 15/A - LASL Report Library

